

SILICON GATE MOS 2500 SERIES

DESCRIPTION

The Signetics 2513 is a high speed 2560-bit Static ROM organized as 64x8x5. A standard 7x5 dot matrix fits well in the 2513. The product uses +5V, -5V and -12V power supplies, TTL level interface signals and Tri-State Outputs for direct, low cost interfacing with TTL, DTL, CMOS and 2500 Series MOS.

FEATURES

- 450 ns TYPICAL ACCESS TIME
- STATIC OPERATION
- TTL/DTL COMPATIBLE INPUTS
- +5, -5, -12V POWER SUPPLIES
- TRI-STATE OUTPUT CONTROLLED BY CHIP ENABLE FOR BUSSING CAPABILITY
- 2513/CM2141 ASCII FONT STANDARD(7X5)
- 24-PIN DIP
- P-MOS SILICON GATE TECHNOLOGY

APPLICATIONS

RASTER SCAN CRT DISPLAYS (ROW OUTPUT)
 PRINTER CHARACTER GENERATOR
 PANEL DISPLAYS AND BILLBOARDS
 MICRO-PROGRAMMING
 CODE CONVERSION

PROCESS TECHNOLOGY

The use of Signetics' P channel Silicon Gate Process allows the design and production of higher functional density and operating speed than other techniques.


SILICONE PACKAGING

Low cost silicone DIP packaging is implemented and reliability is assured by the use of Signetics unique silicon gate MOS process technology. Unlike the standard metal gate MOS process the silicon material over the gate oxide passivates the MOS transistors. In addition, Signetics proprietary surface passivation and silicone packaging techniques result in an MOS circuit with inherent high reliability, superior moisture resistance, and ionic contamination barriers.

BIPOLAR COMPATIBILITY

All inputs of the 2513 can be driven directly by standard TTL voltage levels. The data output buffers are capable of sinking a minimum of 1.6 mA, sufficient to drive one standard TTL load.

PIN CONFIGURATION (Top View)



- | | |
|---------------------|---------------------|
| 1. V _{GG} | 24. V _{CC} |
| 2. NC | 23. NC |
| 3. NC | 22. Address 9 |
| 4. Out 1 | 21. Address 8 |
| 5. Out 2 | 20. Address 7 |
| 6. Out 3 | 19. Address 6 |
| 7. Out 4 | 18. Address 5 |
| 8. Out 5 | 17. Address 4 |
| 9. NC | 16. Address 3 |
| 10. NC | 15. Address 2 |
| 11. Chip Enable | 14. Address 1 |
| 12. V _{DD} | 13. NC |


PART IDENTIFICATION TABLE

PART	ORGANIZATION	PROGRAMMING
2513N/I		
CM2141	64X8X5	ASCII Font
2513N/I	64X7X5	
CMXXXX	64X8X5	Custom

N PACKAGE = 24 PIN SILICONE DIP

I PACKAGE = 24 PIN CERAMIC DIP

CHARACTER FORMAT



MAXIMUM GUARANTEED RATINGS(1)

Operating Ambient Temperature 0°C to 70°C
 Storage Temperature -85°C to +150°C
 Package Power Dissipation(2) @T_A 70°C 730mW
 Input(3) and Supply Voltages
 with respect to V_{CC} +0.3 to -20V

NOTES

1. Stresses above those listed under "Maximum Guaranteed Rating" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or at any other condition above those indicated in the operational sections of this specification is not implied.
2. For operating at elevated temperatures the device must be derated based on a +150°C maximum junction temperature and a thermal resistance of 110°C/W junction to ambient.
3. All inputs are protected against static charge.
4. Parameters are valid over operating temperature range unless specified.
5. All voltage measurements are referenced to ground.
6. Manufacturer reserves the right to make design and process changes and improvements.
7. Typical values are at +25°C and nominal supply voltages.
8. Guaranteed input levels are stated for worst case conditions including a ±5% variation in V_{CC} and a temperature variation of 0°C to +70°C. Actual input requirements with respect to V_{CC} are V_{IH} = V_{CC} - 1.85V and V_{IL} = V_{CC} - 4.15V.

DC CHARACTERISTICS

T_A = 0°C to +70°C; V_{CC} = +5V ±5%; V_{DD} = -5V ±5%; V_{GG} = -12V ±5% unless otherwise noted. (Notes 4, 5, 6, 7)

SYMBOL	TEST	MIN	TYP	MAX	UNIT	CONDITIONS
I _{LI}	Input Load Current		10	500	nA	V _{IN} = -5.5V T _A = 25°C
I _{LO}	Output Leakage Current		10	1000	nA	V _{OUT} = -5.5V T _A = 25°C V _{CE} = V _{CC}
I _{DD}	V _{DD} Power Supply Current		12	15	mA	Outputs Open
I _{GG}	V _{GG} Power Supply Current		10	15	mA	Outputs Open V _{CE} = V _{CC}
V _{IL}	Input Logic "0"			+0.6	V	Note 8
V _{IH}	Input Logic "1"	+3.4		5.3	V	Note 8


SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513

AC CHARACTERISTICS


$T_A = 0^\circ\text{C}$ to $+70^\circ\text{C}$; $V_{CC} = 5\text{V} \pm 5\%$; $V_{DD} = -5\text{V} \pm 5\%$; $V_{GG} = -12\text{V} \pm 5\%$; unless otherwise noted.

SYMBOL	TEST	MIN	TYP	MAX	UNIT	CONDITIONS
V_{OL}	Output Logic "Zero"	-5		0.4	V	One TTL Load
V_{OH}	Output Logic "One"	3.0			V	One TTL Load
$t_{CA}(\text{CM2141})$	Character Access Time		500	600	ns	See AC Test Setup
t_{RA}	Row Access Time ($A_1 - A_3$)		450	500	ns	See AC Test Setup
t_{CE}	Chip Enable to Output		150		ns	
C_{IN}	Address Input Capacitance			10	pF	$f = 1\text{ MHz}$, $V_{IH} = V_{CC}$, 25mV p-p


BLOCK DIAGRAM




TIMING DIAGRAM



AC TEST SETUP




TYPICAL CHARACTERISTIC CURVES




SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513


APPLICATIONS INFORMATION



DTL/TTL INTERFACING




CIRCUIT CROSS-SECTION



ASCII CHARACTER FONT

2513N/CM2141



SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513



COMPANY _____
 ADDRESS _____

 TELEPHONE _____
 AUTHORIZED SIGNATURE _____
 DATE _____
 CUSTOMER PRINT OR ID NO. _____
 PURCHASE ORDER NUMBER _____
 DEVICE TYPE _____ 2513 _____
 CUSTOM PATTERN NUMBER (TO BE ENTERED BY SIGNETICS) _____

ORGANIZATION AS CHARACTER GENERATOR

A six-bit binary address (A_4 through A_9) selects 1-of-64 matrix characters arranged 5 dots horizontally and 8 dots vertically. A three bit binary address code (A_1 through A_3) selects 1 of 8 rows. Five outputs display a complete row of the character matrix. See Figure 1. The devices may also be used in pairs to provide 9 X 7 and 10 X 8 vertical scan formats.

CHARACTER FORMAT



ORGANIZATION AS READ-ONLY MEMORY

For a straight 512 X 5 read-only memory, the five outputs will display any one of 512 5-bit stored words corresponding to a 9-bit address applied to A_1 through A_9 .

CUSTOM DEVICES

For unique custom memory patterns, this form should be used to transmit coding instructions. The nomenclature for a custom device will consist of the basic product type followed by a unique CM number assigned by Signetics. For example, "2513N/CM2141".

■ PROGRAMMING WITH PUNCHED CARDS

For maximum accuracy and minimum cost and turn-around time, the truth table should be transmitted to Signetics in the form of punched cards according to the format indicated on the following pages.

■ PROGRAMMING WITH WRITTEN TRUTH TABLE

When punched data cards cannot be supplied, the truth table may be transmitted in written form using the attached blank truth table.

VERIFICATION

Upon receipt of either punched card or written truth table information, Signetics will prepare a computer tabulation of the instructions and return to the address indicated. If errors are detected, they should be transmitted to Signetics as quickly as possible.

LOGIC CONVENTION

Logic "1"s or blackened squares in the truth table will result in "high" output from the indicated output terminal (i.e. 3.2V minimum). Similarly, a "1" address input level is interpreted as 3.2V minimum.

ADDRESS A9 A8 A7 A6 A5 A4 A3 A2 A1	DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.
		06	04	03	02	01	
0 0 0 0 0 0 0 0 0	000						
0 0 0 0 0 0 0 0 1	001						
0 0 0 0 0 0 0 1 0	002						
0 0 0 0 0 0 0 1 1	003						
0 0 0 0 0 0 1 0 0	004						
0 0 0 0 0 0 1 0 1	005						
0 0 0 0 0 0 1 1 0	006						
0 0 0 0 0 0 1 1 1	007						

ADDRESS A9 A8 A7 A6 A5 A4 A3 A2 A1	DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.
		06	04	03	02	01	
0 0 0 1 0 0 0 0 0	032						
0 0 0 1 0 0 0 0 1	033						
0 0 0 1 0 0 0 1 0	034						
0 0 0 1 0 0 0 1 1	035						
0 0 0 1 0 0 1 0 0	036						
0 0 0 1 0 0 1 0 1	037						
0 0 0 1 0 0 1 1 0	038						
0 0 0 1 0 0 1 1 1	039						

0 0 0 0 0 1 0 0 0	008						
0 0 0 0 0 1 0 0 1	009						
0 0 0 0 0 1 0 1 0	010						
0 0 0 0 0 1 0 1 1	011						
0 0 0 0 0 1 1 0 0	012						
0 0 0 0 0 1 1 0 1	013						
0 0 0 0 0 1 1 1 0	014						
0 0 0 0 0 1 1 1 1	015						

0 0 0 1 0 1 0 0 0	040						
0 0 0 1 0 1 0 0 1	041						
0 0 0 1 0 1 0 1 0	042						
0 0 0 1 0 1 0 1 1	043						
0 0 0 1 0 1 1 0 0	044						
0 0 0 1 0 1 1 0 1	045						
0 0 0 1 0 1 1 1 0	046						
0 0 0 1 0 1 1 1 1	047						

0 0 0 0 1 0 0 0 0	016						
0 0 0 0 1 0 0 0 1	017						
0 0 0 0 1 0 0 1 0	018						
0 0 0 0 1 0 0 1 1	019						
0 0 0 0 1 0 1 0 0	020						
0 0 0 0 1 0 1 0 1	021						
0 0 0 0 1 0 1 1 0	022						
0 0 0 0 1 0 1 1 1	023						

0 0 0 1 1 0 0 0 0	048						
0 0 0 1 1 0 0 0 1	049						
0 0 0 1 1 0 0 1 0	050						
0 0 0 1 1 0 0 1 1	051						
0 0 0 1 1 0 1 0 0	052						
0 0 0 1 1 0 1 0 1	053						
0 0 0 1 1 0 1 1 0	054						
0 0 0 1 1 0 1 1 1	055						

0 0 0 0 1 1 0 0 0	024						
0 0 0 0 1 1 0 0 1	025						
0 0 0 0 1 1 0 1 0	026						
0 0 0 0 1 1 0 1 1	027						
0 0 0 0 1 1 1 0 0	028						
0 0 0 0 1 1 1 0 1	029						
0 0 0 0 1 1 1 1 0	030						
0 0 0 0 1 1 1 1 1	031						

0 0 0 1 1 1 0 0 0	056						
0 0 0 1 1 1 0 0 1	057						
0 0 0 1 1 1 0 1 0	058						
0 0 0 1 1 1 0 1 1	059						
0 0 0 1 1 1 1 0 0	060						
0 0 0 1 1 1 1 0 1	061						
0 0 0 1 1 1 1 1 0	062						
0 0 0 1 1 1 1 1 1	063						

SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513

ADDRESS A8 A7 A6 A5 A4 A3 A2 A1	DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.
		05	04	03	02	01	
0 0 1 0 0 0 0 0 0	064						
0 0 1 0 0 0 0 0 1	065						
0 0 1 0 0 0 0 1 0	066						
0 0 1 0 0 0 0 1 1	067						
0 0 1 0 0 0 1 0 0	068						
0 0 1 0 0 0 1 0 1	069						
0 0 1 0 0 0 1 1 0	070						
0 0 1 0 0 0 1 1 1	071						

ADDRESS A8 A7 A6 A5 A4 A3 A2 A1	DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.
		05	04	03	02	01	
0 0 1 1 0 0 0 0 0	096						
0 0 1 1 0 0 0 0 1	097						
0 0 1 1 0 0 0 1 0	098						
0 0 1 1 0 0 0 1 1	099						
0 0 1 1 0 0 1 0 0	100						
0 0 1 1 0 0 1 0 1	101						
0 0 1 1 0 0 1 1 0	102						
0 0 1 1 0 0 1 1 1	103						

0 0 1 0 0 1 0 0 0	072						
0 0 1 0 0 1 0 0 1	073						
0 0 1 0 0 1 0 1 0	074						
0 0 1 0 0 1 0 1 1	075						
0 0 1 0 0 1 1 0 0	076						
0 0 1 0 0 1 1 0 1	077						
0 0 1 0 0 1 1 1 0	078						
0 0 1 0 0 1 1 1 1	079						

0 0 1 1 0 1 0 0 0	104						
0 0 1 1 0 1 0 0 1	105						
0 0 1 1 0 1 0 1 0	106						
0 0 1 1 0 1 0 1 1	107						
0 0 1 1 0 1 1 0 0	108						
0 0 1 1 0 1 1 0 1	109						
0 0 1 1 0 1 1 1 0	110						
0 0 1 1 0 1 1 1 1	111						

0 0 1 0 1 0 0 0 0	080						
0 0 1 0 1 0 0 0 1	081						
0 0 1 0 1 0 0 1 0	082						
0 0 1 0 1 0 0 1 1	083						
0 0 1 0 1 0 1 0 0	084						
0 0 1 0 1 0 1 0 1	085						
0 0 1 0 1 0 1 1 0	086						
0 0 1 0 1 0 1 1 1	087						

0 0 1 1 1 0 0 0 0	112						
0 0 1 1 1 0 0 0 1	113						
0 0 1 1 1 0 0 1 0	114						
0 0 1 1 1 0 0 1 1	115						
0 0 1 1 1 0 1 0 0	116						
0 0 1 1 1 0 1 0 1	117						
0 0 1 1 1 0 1 1 0	118						
0 0 1 1 1 0 1 1 1	119						

0 0 1 0 1 1 0 0 0	088						
0 0 1 0 1 1 0 0 1	089						
0 0 1 0 1 1 0 1 0	090						
0 0 1 0 1 1 0 1 1	091						
0 0 1 0 1 1 1 0 0	092						
0 0 1 0 1 1 1 0 1	093						
0 0 1 0 1 1 1 1 0	094						
0 0 1 0 1 1 1 1 1	095						

0 0 1 1 1 1 0 0 0	120						
0 0 1 1 1 1 0 0 1	121						
0 0 1 1 1 1 0 1 0	122						
0 0 1 1 1 1 0 1 1	123						
0 0 1 1 1 1 1 0 0	124						
0 0 1 1 1 1 1 0 1	125						
0 0 1 1 1 1 1 1 0	126						
0 0 1 1 1 1 1 1 1	127						

SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513

ADDRESS								DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.	
A9	A8	A7	A6	A5	A4	A3	A2		A1	05	04	03	02		01
0	1	0	0	0	0	0	0	0	128						
0	1	0	0	0	0	0	0	1	129						
0	1	0	0	0	0	0	1	0	130						
0	1	0	0	0	0	0	1	1	131						
0	1	0	0	0	0	1	0	0	132						
0	1	0	0	0	0	1	0	1	133						
0	1	0	0	0	0	1	1	0	134						
0	1	0	0	0	0	1	1	1	135						

ADDRESS								DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.	
A9	A8	A7	A6	A5	A4	A3	A2		A1	05	04	03	02		01
0	1	0	1	0	0	0	0	0	160						
0	1	0	1	0	0	0	0	1	161						
0	1	0	1	0	0	0	1	0	162						
0	1	0	1	0	0	0	1	1	163						
0	1	0	1	0	0	1	0	0	164						
0	1	0	1	0	0	1	0	1	165						
0	1	0	1	0	0	1	1	0	166						
0	1	0	1	0	0	1	1	1	167						

0	1	0	0	0	1	0	0	0	136						
0	1	0	0	0	1	0	0	1	137						
0	1	0	0	0	1	0	1	0	138						
0	1	0	0	0	1	0	1	1	139						
0	1	0	0	0	1	1	0	0	140						
0	1	0	0	0	1	1	0	1	141						
0	1	0	0	0	1	1	1	0	142						
0	1	0	0	0	1	1	1	1	143						

0	1	0	1	0	1	0	0	0	168						
0	1	0	1	0	1	0	0	1	169						
0	1	0	1	0	1	0	1	0	170						
0	1	0	1	0	1	0	1	1	171						
0	1	0	1	0	1	1	0	0	172						
0	1	0	1	0	1	1	0	1	173						
0	1	0	1	0	1	1	1	0	174						
0	1	0	1	0	1	1	1	1	175						

0	1	0	0	1	0	0	0	0	144						
0	1	0	0	1	0	0	0	1	145						
0	1	0	0	1	0	0	1	0	146						
0	1	0	0	1	0	0	1	1	147						
0	1	0	0	1	0	1	0	0	148						
0	1	0	0	1	0	1	0	1	149						
0	1	0	0	1	0	1	1	0	150						
0	1	0	0	1	0	1	1	1	151						

0	1	0	1	1	0	0	0	0	176						
0	1	0	1	1	0	0	0	1	177						
0	1	0	1	1	0	0	1	0	178						
0	1	0	1	1	0	0	1	1	179						
0	1	0	1	1	0	1	0	0	180						
0	1	0	1	1	0	1	0	1	181						
0	1	0	1	1	0	1	1	0	182						
0	1	0	1	1	0	1	1	1	183						

0	1	0	0	1	1	0	0	0	152						
0	1	0	0	1	1	0	0	1	153						
0	1	0	0	1	1	0	1	0	154						
0	1	0	0	1	1	0	1	1	155						
0	1	0	0	1	1	1	0	0	156						
0	1	0	0	1	1	1	0	1	157						
0	1	0	0	1	1	1	1	0	158						
0	1	0	0	1	1	1	1	1	159						

0	1	0	1	1	1	0	0	0	184						
0	1	0	1	1	1	0	0	1	185						
0	1	0	1	1	1	0	1	0	186						
0	1	0	1	1	1	0	1	1	187						
0	1	0	1	1	1	1	0	0	188						
0	1	0	1	1	1	1	0	1	189						
0	1	0	1	1	1	1	1	0	190						
0	1	0	1	1	1	1	1	1	191						

SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR - 2513

ADDRESS							DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.	
A9	A8	A7	A6	A5	A4	A3		A2	A1	D5	D4	D3		D2
0	1	1	0	0	0	0	0	0						
0	1	1	0	0	0	0	0	1						
0	1	1	0	0	0	0	1	0						
0	1	1	0	0	0	0	1	1						
0	1	1	0	0	0	1	0	0						
0	1	1	0	0	0	1	0	1						
0	1	1	0	0	0	1	1	0						
0	1	1	0	0	0	1	1	1						

ADDRESS							DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.	
A9	A8	A7	A6	A5	A4	A3		A2	A1	D5	D4	D3		D2
0	1	1	1	0	0	0	0	0						
0	1	1	1	0	0	0	0	1						
0	1	1	1	0	0	0	1	0						
0	1	1	1	0	0	0	1	1						
0	1	1	1	0	0	1	0	0						
0	1	1	1	0	0	1	0	1						
0	1	1	1	0	0	1	1	0						
0	1	1	1	0	0	1	1	1						

0	1	1	0	0	1	0	0	0	200					
0	1	1	0	0	1	0	0	1	201					
0	1	1	0	0	1	0	1	0	202					
0	1	1	0	0	1	0	1	1	203					
0	1	1	0	0	1	1	0	0	204					
0	1	1	0	0	1	1	0	1	205					
0	1	1	0	0	1	1	1	0	206					
0	1	1	0	0	1	1	1	1	207					

0	1	1	1	0	1	0	0	0	232					
0	1	1	1	0	1	0	0	1	233					
0	1	1	1	0	1	0	1	0	234					
0	1	1	1	0	1	0	1	1	235					
0	1	1	1	0	1	1	0	0	236					
0	1	1	1	0	1	1	0	1	237					
0	1	1	1	0	1	1	1	0	238					
0	1	1	1	0	1	1	1	1	239					

0	1	1	0	1	0	0	0	0	208					
0	1	1	0	1	0	0	0	1	209					
0	1	1	0	1	0	0	1	0	210					
0	1	1	0	1	0	0	1	1	211					
0	1	1	0	1	0	1	0	0	212					
0	1	1	0	1	0	1	0	1	213					
0	1	1	0	1	0	1	1	0	214					
0	1	1	0	1	0	1	1	1	215					

0	1	1	1	1	0	0	0	0	240					
0	1	1	1	1	0	0	0	1	241					
0	1	1	1	1	0	0	1	0	242					
0	1	1	1	1	0	0	1	1	243					
0	1	1	1	1	0	1	0	0	244					
0	1	1	1	1	0	1	0	1	245					
0	1	1	1	1	0	1	1	0	246					
0	1	1	1	1	0	1	1	1	247					

0	1	1	0	1	1	0	0	0	216					
0	1	1	0	1	1	0	0	1	217					
0	1	1	0	1	1	0	1	0	218					
0	1	1	0	1	1	0	1	1	219					
0	1	1	0	1	1	1	0	0	220					
0	1	1	0	1	1	1	0	1	221					
0	1	1	0	1	1	1	1	0	222					
0	1	1	0	1	1	1	1	1	223					

0	1	1	1	1	1	0	0	0	248					
0	1	1	1	1	1	0	0	1	249					
0	1	1	1	1	1	0	1	0	250					
0	1	1	1	1	1	0	1	1	251					
0	1	1	1	1	1	1	0	0	252					
0	1	1	1	1	1	1	0	1	253					
0	1	1	1	1	1	1	1	0	254					
0	1	1	1	1	1	1	1	1	255					

SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513

ADDRESS								DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.
A9	A8	A7	A6	A5	A4	A3	A2		A1	O5	O4	O3	O2	
1	0	0	0	0	0	0	0	0	256					
1	0	0	0	0	0	0	0	1	257					
1	0	0	0	0	0	0	1	0	258					
1	0	0	0	0	0	0	1	1	259					
1	0	0	0	0	1	0	0		260					
1	0	0	0	0	1	0	1		261					
1	0	0	0	0	1	1	0		262					
1	0	0	0	0	1	1	1		263					

ADDRESS								DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.
A8	A7	A6	A5	A4	A3	A2	A1		O5	O4	O3	O2	O1	
1	0	0	1	0	0	0	0	0	268					
1	0	0	1	0	0	0	0	1	269					
1	0	0	1	0	0	0	1	0	270					
1	0	0	1	0	0	0	1	1	271					
1	0	0	1	0	0	1	0	0	272					
1	0	0	1	0	0	1	0	1	273					
1	0	0	1	0	0	1	0	1	274					
1	0	0	1	0	0	1	1	0	275					
1	0	0	1	0	0	1	1	1	276					
1	0	0	1	0	1	0	0		277					
1	0	0	1	0	1	0	1		278					
1	0	0	1	0	1	0	1	1	279					

1	0	0	0	0	1	0	0	0	264					
1	0	0	0	0	1	0	0	1	265					
1	0	0	0	0	1	0	1	0	266					
1	0	0	0	0	1	0	1	1	267					
1	0	0	0	0	1	1	0	0	268					
1	0	0	0	0	1	1	0	1	269					
1	0	0	0	0	1	1	1	0	270					
1	0	0	0	0	1	1	1	1	271					

1	0	0	1	0	1	0	0	0	296					
1	0	0	1	0	1	0	0	0	297					
1	0	0	1	0	1	0	0	1	298					
1	0	0	1	0	1	0	1	0	299					
1	0	0	1	0	1	0	1	1	300					
1	0	0	1	0	1	1	0	0	301					
1	0	0	1	0	1	1	0	1	302					
1	0	0	1	0	1	1	1	0	303					

1	0	0	0	1	0	0	0	0	272					
1	0	0	0	1	0	0	0	1	273					
1	0	0	0	1	0	0	1	0	274					
1	0	0	0	1	0	0	1	1	275					
1	0	0	0	1	0	1	0	0	276					
1	0	0	0	1	0	1	0	1	277					
1	0	0	0	1	0	1	1	0	278					
1	0	0	0	1	0	1	1	1	279					

1	0	0	1	1	0	0	0	0	304					
1	0	0	1	1	0	0	0	1	305					
1	0	0	1	1	0	0	1	0	306					
1	0	0	1	1	0	0	1	1	307					
1	0	0	1	1	0	1	0	0	308					
1	0	0	1	1	0	1	0	1	309					
1	0	0	1	1	0	1	1	0	310					
1	0	0	1	1	0	1	1	1	311					

1	0	0	0	1	1	0	0	0	280					
1	0	0	0	1	1	0	0	1	281					
1	0	0	0	1	1	0	1	0	282					
1	0	0	0	1	1	0	1	1	283					
1	0	0	0	1	1	1	0	0	284					
1	0	0	0	1	1	1	0	1	285					
1	0	0	0	1	1	1	1	0	286					
1	0	0	0	1	1	1	1	1	287					

1	0	0	1	1	1	0	0	0	312					
1	0	0	1	1	1	0	0	1	313					
1	0	0	1	1	1	0	1	0	314					
1	0	0	1	1	1	0	1	1	315					
1	0	0	1	1	1	1	0	0	316					
1	0	0	1	1	1	1	0	1	317					
1	0	0	1	1	1	1	1	0	318					
1	0	0	1	1	1	1	1	1	319					

SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513

ADDRESS							DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.
A8	A7	A6	A5	A4	A3	A2		A1	05	04	03	02	
1	0	1	0	0	0	0	0	320					
1	0	1	0	0	0	0	1	321					
1	0	1	0	0	0	1	0	322					
1	0	1	0	0	0	1	1	323					
1	0	1	0	0	1	0	0	324					
1	0	1	0	0	1	0	1	325					
1	0	1	0	0	1	1	0	326					
1	0	1	0	0	1	1	1	327					

ADDRESS							DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.
A8	A7	A6	A5	A4	A3	A2		A1	05	04	03	02	
1	0	1	1	0	0	0	0	382					
1	0	1	1	0	0	0	1	383					
1	0	1	1	0	0	1	0	384					
1	0	1	1	0	0	1	1	385					
1	0	1	1	0	1	0	0	386					
1	0	1	1	0	1	0	1	387					
1	0	1	1	0	1	1	0	388					
1	0	1	1	0	1	1	1	389					

1	0	1	0	0	1	0	0	328					
1	0	1	0	0	1	0	1	329					
1	0	1	0	0	1	0	1	330					
1	0	1	0	0	1	0	1	331					
1	0	1	0	0	1	1	0	332					
1	0	1	0	0	1	1	0	333					
1	0	1	0	0	1	1	1	334					
1	0	1	0	0	1	1	1	335					

1	0	1	1	0	1	0	0	360					
1	0	1	1	0	1	0	1	361					
1	0	1	1	0	1	0	1	362					
1	0	1	1	0	1	0	1	363					
1	0	1	1	0	1	1	0	364					
1	0	1	1	0	1	1	0	365					
1	0	1	1	0	1	1	1	366					
1	0	1	1	0	1	1	1	367					

1	0	1	0	1	0	0	0	336					
1	0	1	0	1	0	0	1	337					
1	0	1	0	1	0	0	1	338					
1	0	1	0	1	0	0	1	339					
1	0	1	0	1	0	1	0	340					
1	0	1	0	1	0	1	0	341					
1	0	1	0	1	0	1	1	342					
1	0	1	0	1	0	1	1	343					

1	0	1	1	1	0	0	0	368					
1	0	1	1	1	0	0	1	369					
1	0	1	1	1	0	0	1	370					
1	0	1	1	1	0	0	1	371					
1	0	1	1	1	0	1	0	372					
1	0	1	1	1	0	1	0	373					
1	0	1	1	1	0	1	1	374					
1	0	1	1	1	0	1	1	375					

1	0	1	0	1	1	0	0	344					
1	0	1	0	1	1	0	1	345					
1	0	1	0	1	1	0	1	346					
1	0	1	0	1	1	0	1	347					
1	0	1	0	1	1	1	0	348					
1	0	1	0	1	1	1	0	349					
1	0	1	0	1	1	1	1	350					
1	0	1	0	1	1	1	1	351					

1	0	1	1	1	1	0	0	376					
1	0	1	1	1	1	0	1	377					
1	0	1	1	1	1	0	1	378					
1	0	1	1	1	1	0	1	379					
1	0	1	1	1	1	1	0	380					
1	0	1	1	1	1	1	0	381					
1	0	1	1	1	1	1	1	382					
1	0	1	1	1	1	1	1	383					

SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513

ADDRESS								DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.	
A8	A8	A7	A6	A5	A4	A3	A2		A1	05	04	03	02		01
1	1	0	0	0	0	0	0	0	384						
1	1	0	0	0	0	0	0	1	385						
1	1	0	0	0	0	0	1	0	386						
1	1	0	0	0	0	0	1	1	387						
1	1	0	0	0	0	1	0	0	388						
1	1	0	0	0	0	1	0	1	389						
1	1	0	0	0	0	1	1	0	390						
1	1	0	0	0	0	1	1	1	391						

ADDRESS								DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.	
A8	A8	A7	A6	A5	A4	A3	A2		A1	05	04	03	02		01
1	1	0	1	0	0	0	0	0	416						
1	1	0	1	0	0	0	0	1	417						
1	1	0	1	0	0	0	1	0	418						
1	1	0	1	0	0	0	1	1	419						
1	1	0	1	0	0	1	0	0	420						
1	1	0	1	0	0	1	0	1	421						
1	1	0	1	0	0	1	1	0	422						
1	1	0	1	0	0	1	1	1	423						

1	1	0	0	0	1	0	0	0	392						
1	1	0	0	0	1	0	0	1	393						
1	1	0	0	0	1	0	1	0	394						
1	1	0	0	0	1	0	1	1	395						
1	1	0	0	0	1	1	0	0	396						
1	1	0	0	0	1	1	0	1	397						
1	1	0	0	0	1	1	1	0	398						
1	1	0	0	0	1	1	1	1	399						

1	1	0	1	0	1	0	0	0	424						
1	1	0	1	0	1	0	0	1	425						
1	1	0	1	0	1	0	1	0	426						
1	1	0	1	0	1	0	1	1	427						
1	1	0	1	0	1	1	0	0	428						
1	1	0	1	0	1	1	0	1	429						
1	1	0	1	0	1	1	1	0	430						
1	1	0	1	0	1	1	1	1	431						

1	1	0	0	1	0	0	0	0	400						
1	1	0	0	1	0	0	0	1	401						
1	1	0	0	1	0	0	1	0	402						
1	1	0	0	1	0	0	1	1	403						
1	1	0	0	1	0	1	0	0	404						
1	1	0	0	1	0	1	0	1	405						
1	1	0	0	1	0	1	1	0	406						
1	1	0	0	1	0	1	1	1	407						

1	1	0	1	1	0	0	0	0	432						
1	1	0	1	1	0	0	0	1	433						
1	1	0	1	1	0	0	1	0	434						
1	1	0	1	1	0	0	1	1	435						
1	1	0	1	1	0	1	0	0	436						
1	1	0	1	1	0	1	0	1	437						
1	1	0	1	1	0	1	1	0	438						
1	1	0	1	1	0	1	1	1	439						

1	1	0	0	1	1	0	0	0	408						
1	1	0	0	1	1	0	0	1	409						
1	1	0	0	1	1	0	1	0	410						
1	1	0	0	1	1	0	1	1	411						
1	1	0	0	1	1	1	0	0	412						
1	1	0	0	1	1	1	0	1	413						
1	1	0	0	1	1	1	1	0	414						
1	1	0	0	1	1	1	1	1	415						

1	1	0	1	1	1	0	0	0	440						
1	1	0	1	1	1	0	0	1	441						
1	1	0	1	1	1	0	1	0	442						
1	1	0	1	1	1	0	1	1	443						
1	1	0	1	1	1	1	0	0	444						
1	1	0	1	1	1	1	0	1	445						
1	1	0	1	1	1	1	1	0	446						
1	1	0	1	1	1	1	1	1	447						

SIGNETICS 64 X 8 X 5 CHARACTER GENERATOR ■ 2513

ADDRESS							DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.	
A9	A8	A7	A6	A5	A4	A3		A2	A1	05	04	03		02
1	1	1	0	0	0	0	0	0	448					
1	1	1	0	0	0	0	0	1	449					
1	1	1	0	0	0	0	1	0	450					
1	1	1	0	0	0	0	1	1	451					
1	1	1	0	0	0	1	0	0	452					
1	1	1	0	0	0	1	0	1	453					
1	1	1	0	0	0	1	1	0	454					
1	1	1	0	0	0	1	1	1	455					

ADDRESS							DECIMAL ADDRESS	OUTPUT DATA					USER'S CHAR.	
A9	A8	A7	A6	A5	A4	A3		A2	A1	05	04	03		02
1	1	1	1	0	0	0	0	0	480					
1	1	1	1	0	0	0	0	1	481					
1	1	1	1	0	0	0	1	0	482					
1	1	1	1	0	0	0	1	1	483					
1	1	1	1	0	0	1	0	0	484					
1	1	1	1	0	0	1	0	1	485					
1	1	1	1	0	0	1	1	0	486					
1	1	1	1	0	0	1	1	1	487					

1	1	1	0	0	1	0	0	0	456					
1	1	1	0	0	1	0	0	1	457					
1	1	1	0	0	1	0	1	0	458					
1	1	1	0	0	1	0	1	1	459					
1	1	1	0	0	1	1	0	0	460					
1	1	1	0	0	1	1	0	1	461					
1	1	1	0	0	1	1	1	0	462					
1	1	1	0	0	1	1	1	1	463					

1	1	1	1	0	1	0	0	0	488					
1	1	1	1	0	1	0	0	1	489					
1	1	1	1	0	1	0	1	0	490					
1	1	1	1	0	1	0	1	1	491					
1	1	1	1	0	1	1	0	0	492					
1	1	1	1	0	1	1	0	1	493					
1	1	1	1	0	1	1	1	0	494					
1	1	1	1	0	1	1	1	1	495					

1	1	1	0	1	0	0	0	0	464					
1	1	1	0	1	0	0	0	1	465					
1	1	1	0	1	0	0	1	0	466					
1	1	1	0	1	0	0	1	1	467					
1	1	1	0	1	0	1	0	0	468					
1	1	1	0	1	0	1	0	1	469					
1	1	1	0	1	0	1	1	0	470					
1	1	1	0	1	0	1	1	1	471					

1	1	1	1	1	0	0	0	0	496					
1	1	1	1	1	0	0	0	1	497					
1	1	1	1	1	0	0	1	0	498					
1	1	1	1	1	0	0	1	1	499					
1	1	1	1	1	0	1	0	0	500					
1	1	1	1	1	0	1	0	1	501					
1	1	1	1	1	0	1	1	0	502					
1	1	1	1	1	0	1	1	1	503					

1	1	1	0	1	1	0	0	0	472					
1	1	1	0	1	1	0	0	1	473					
1	1	1	0	1	1	0	1	0	474					
1	1	1	0	1	1	0	1	1	475					
1	1	1	0	1	1	1	0	0	476					
1	1	1	0	1	1	1	0	1	477					
1	1	1	0	1	1	1	1	0	478					
1	1	1	0	1	1	1	1	1	479					

1	1	1	1	1	1	0	0	0	504					
1	1	1	1	1	1	0	0	1	505					
1	1	1	1	1	1	0	1	0	506					
1	1	1	1	1	1	0	1	1	507					
1	1	1	1	1	1	1	0	0	508					
1	1	1	1	1	1	1	0	1	509					
1	1	1	1	1	1	1	1	0	510					
1	1	1	1	1	1	1	1	1	511					